

AudioControl®

Making Good Sound Great™

AUDIOCONTROL MICRO AMPLIFIERS



ACM-4.300™

FOUR CHANNEL MICRO AMPLIFIER

75 WATTS X 4 @ 2 OHMS | 50 WATTS X 4 @ 4 OHMS | 150 WATTS BRIDGED

SPEAKER-LEVEL INPUTS | LINE LEVEL INPUTS | GTO™ SIGNAL SENSE

LINKWITZ-RILEY CROSSOVER | FLEXIBLE MOUNTING OPTIONS

MOBILE ELECTRONICS

AUDIOCONTROL FOUR CHANNEL MICRO AMPLIFIER

ACM series amplifiers by AudioControl are the perfect blend of power and features for car audio systems from mild to wild. Compact size, high power and the ability to help integrate with factory stereo systems are features that assure "Making Good Sound Great" can happen in any installation. Reversible cover plates allow flexible mounting options when paired with AudioControl DM Series Processors or when using multiple ACM series amplifiers in confined spaces. Once again AudioControl comes to the rescue combining features and benefits needed to assure audio euphoria in an automotive setting.

- Four Channel Micro Amplifier
- 75 W @ 2 ohms
- 50 W @ 4 ohms
- 150 W @ 4 ohms bridged
- Speaker Level Inputs / RCA Line Inputs
- GTO™ Signal Sense
- Linkwitz-Riley Crossover
- Reversible Cover Plate
- Flexible Mounting Options

ACM FOUR CHANNEL AMPLIFIER	Inputs		Continuous Power (RMS) at 14.4V	Maximum Input Voltage	S/N Ratio (ref: rated power)	THD+N	Frequency Response	Linkwitz-Riley Crossover (selectable)	PFM Subsonic Filter
	Speaker Level	Line Level							
ACM-4.300™	2	2	50W @ 4Ω 75W @ 2Ω 150W @ 4Ω Bridged	500 mV - 6 Vrms	102 dBa	<0.01%	10 Hz - 22 kHz	12 dB/octave 80 Hz / 120 Hz / Bypass	32 Hz



ACM-4.300
Shown with reversible cover plate