

AudioControl®

Making Good Sound Great™

“EVERYTHING ELSE IS JUST AN AMPLIFIER”



**THE EPICENTER®
600**



**THE EPICENTER®
1200**



AUDIOCONTROL HIGH-POWER SUBWOOFER AMPLIFIERS

HIGH CURRENT DESIGN 🎵 1 OHM STABLE 🎵 600 WATTS @ 1 OHM (THE EPICENTER® 600 AMPLIFIER)
1200 WATTS @ 1 OHM (THE EPICENTER® 1200 AMPLIFIER) 🎵 THE EPICENTER® DIGITAL BASS RESTORATION
M.I.L.C.™ LEVEL MATCHING (PATENT PENDING) 🎵 24 DB/OCTAVE LINKWITZ-RILEY ALIGNMENT CROSSOVER
GTO SIGNAL SENSE 🎵 PFM SUBSONIC FILTER 🎵 LINE-LEVEL RCA AND SPEAKER-LEVEL INPUTS
ONE-PIECE ALUMINUM CHASSIS 🎵 REMOTE CONTROL FOR LEVEL AND THE EPICENTER® EFFECT

MOBILE ELECTRONICS

AUDIOCONTROL HIGH-POWER SUBWOOFER AMPLIFIERS

When car audio systems demand high levels of subwoofer power output into difficult loads, and a wide range of adjustment to optimize the subwoofer performance within the system, the AudioControl EPICENTER® 600 and 1200 power amplifiers are ideal solutions. Each model delivers high current, stable down to 1 Ohm, and each has a removable top cover that allows access to controls for THE EPICENTER® effect, crossover frequency, gain, polarity, subsonic filter, signal sense, and expansion bus mode.

- High Current Design - 1 Ohm stable
- 600 Watts @ 1 Ohm (THE EPICENTER® 600)
- 1200 Watts @ 1 Ohm (THE EPICENTER® 1200)
- THE EPICENTER Digital Bass Restoration
- M.I.L.C.™ Level Matching Technology (Patent Pending)
- 24 dB/octave Linkwitz-Riley Alignment Crossover
- GTO Signal Sense
- PFM Subsonic Filter
- Line-Level RCA Inputs and Speaker-Level Inputs
- Solid One-Piece Aluminum Chassis
- Remote Control for both Subwoofer Level and THE EPICENTER® effect (ACR-3)
- 5 Year Warranty

FEATURE	THE EPICENTER® 600 AMPLIFIER
POWER OUTPUT (@ 14.4 V)	200 WATTS @ 4 OHMS, 350 WATTS @ 2 OHMS, 600 WATTS @ 1 OHM
S/N RATIO	104 DBA, REF 600 W @ 1 OHM
DAMPING FACTOR	670 @ 10 VOLTS, 4 OHMS OUTPUT, 100 HZ
BASS PROCESSING	THE EPICENTER®
MINIMUM POWER / GROUND WIRE GAUGE	3 GAUGE
FUSE RATING	2 X 30 AMPS
CROSSOVER	24 DB/OCTAVE LINKWITZ-RILEY ADJUSTABLE FROM 30 - 250 HZ
PFM SUBSONIC FILTER	18 DB/OCTAVE, SELECTABLE 16/32 HZ
WEIGHT	4.5 POUNDS
DIMENSIONS	9" W x 7.95" D x 2.1" H

FEATURE	THE EPICENTER® 1200 AMPLIFIER
POWER OUTPUT (@ 14.4 V)	400 WATTS @ 4 OHMS, 750 WATTS @ 2 OHMS, 1200 WATTS @ 1 OHM
S/N RATIO	107 DBA, REF 1200 W @ 1 OHM
DAMPING FACTOR	770 @ 10 VOLTS, 4 OHMS OUTPUT, 100 HZ
BASS PROCESSING	THE EPICENTER®
MINIMUM POWER / GROUND WIRE GAUGE	0 GAUGE
FUSE RATING	3 X 40 AMPS
CROSSOVER	24 DB/OCTAVE LINKWITZ-RILEY ADJUSTABLE FROM 30 - 250 HZ
PFM SUBSONIC FILTER	18 DB/OCTAVE, SELECTABLE 16/32 HZ
WEIGHT	6.6 POUNDS
DIMENSIONS	12" W x 7.95" D x 2.1" H



**THE EPICENTER®
1200**

**THE EPICENTER®
600**



Contact AudioControl
22410 70th Avenue West
Seattle, WA 98043

Tel. 425-775-8461 | Fax 425-778-3166
sound.great@audiocontrol.com
www.audiocontrol.com



AudioControl®
Making Good Sound Great™
©2015. All rights reserved. AudioControl Inc.