

AudioControl®

Making Good Sound Great™

*"I HAVEN'T HEARD AN AMPLIFIER AT ANY PRICE
THAT I'D RATHER LISTEN TO THAN THIS AMPLIFIER"*

- DOUG BLACKBURN ON THE SAVOY G3; WIDESCREEN REVIEW



Premium Theater Amplifiers

UNPARALLELED POWER AND ENERGY EFFICIENCY 🎵 HIGH DEFINITION BiMOS OUTPUTS
COOL RUNNING CLASS H OPERATION 🎵 LIGHTDRIVE™ ANTI-CLIPPING PROTECTION
5 WAY BINDING POSTS 🎵 BALANCED AND UNBALANCED INPUTS
PERFECT MATCH WITH THE MAESTRO M9™ AND MAESTRO M5™

HOME THEATER

PREMIUM CLASS H HOME THEATER AMPLIFIERS

AudioControl Home Theater Amplifiers offer pristine audio performance, incorporating a unique and highly efficient Class H design which achieves well over 200 watts per channel, all channels driven.

The Class H design topology provides increased efficiency and bullet-proof reliability, while reducing heat and unnecessary power dissipation. All Theater Amplifiers feature AudioControl's LightDrive™ Anti-Clipping Protection Circuit, which safely eliminates any possibility of speaker-damaging clipping and distortion, even in extreme conditions.

AudioControl Theater Amplifiers support balanced XLR and unbalanced RCA connections, pass through outputs, Remote Power Control triggers and feature audiophile grade five-way binding posts to guarantee the optimum connection to your speakers.

Designed as a perfect match to AudioControl's Maestro M9 and M5 preamp processors or as standalone critical listening power amplifiers, AudioControl Theater Amplifiers can be easily configured for anything from a powerful 2 channel listening room to an impressively detailed and dynamic multichannel home theater.



From top to bottom: Avalon G4, Avalon G4 rear connections, Pantages G3 rear connections, Savoy G3 rear connections

MODEL	CHANNELS	RACK SIZE	POWER LEVEL			MINIMUM SPEAKER LOAD	FREQ. RESPONSE	S/N RATIO	THD	INPUTS	LOOP OUTPUTS	CROSS-OVERS
			8Ω	4Ω	BRIDGED (8Ω)							
AVALON G3	4	2U	230 W	≈300 W	600 W	4Ω	10 HZ - 20 KHZ	>110 DB, A-WTD, REF. FULL OUTPUT	.015%	4X XLR 4X RCA	4X RCA	VARIABLE HP/LP
PANTAGES G3	5	3U	230 W	≈300 W	NA	4Ω	10 HZ - 20 KHZ	>110 DB, A-WTD, REF. FULL OUTPUT	.05%	5X XLR 5X RCA	NA	NA
SAVOY G3	7	4U	203 W	≈300 W	NA	4Ω	10 HZ - 20 KHZ	>110 DB, A-WTD, REF. FULL OUTPUT	.06%	7X XLR 7X RCA	7X RCA	NA