

Making Good Sound Great™

BRING YOUR MUSIC TO LIFE



SPIKE™ SERIES SUBWOOFERS

HIGH EXCURSION DESIGN | FIBER MATRIX PAPER CONE WITH MICA COATING

3-LAYER HIGH TEMP VOICE COIL FORMER | DUAL DAMPING SYSTEM

DUAL DUST CAP SYSTEM | EFFICIENT HEAVY-DUTY MOTOR DESIGN | REMOVABLE GRILLE INCLUDED

MOBILE ELECTRONICS

SPIKE SERIES SUBWOOFERS

Are you a music fan who loves that low-end rumble? If so, look no further than the Spike Series Subwoofers! For over 45 years, we've been helping people take their car audio to the next level - and our latest product line is sure to enhance any vehicle's sound system. We are proud to present the ultimate in versatility and durability with AudioControl's Spike Series Subwoofers. These high-performance subwoofers come in a variety of sizes and power ratings to suit your audio needs. No matter what type of music you enjoy, Spike will take your listening experience to the next level. These subwoofers were designed to provide clear, precise bass for an immersive listening experience, so why wait? Load up your trunk with Spike Series Subwoofers today, and crank up your listening pleasure!

- High Excursion Design for Ultra Low Bass
- Fiber Matrix Paper Cone with Mica Coating
- 3-Layer High Temp Voice Coil Former
- Dual Damping System for Linear Bass Reproduction
- Dual Dust Cap System for Enclosure Compression Control
- Efficient Heavy-Duty Motor Design
- Removable Subwoofer Grille Included

MODEL	Size	Nominal Impedance	Power Range	Frequency Response	Sensitivity 1W/M (SPL)	Linear Excursion (Xmax)	Mounting Depth	Driver Displacement	Ported Enclosure Range (cu ft)	Sealed Enclosure Range (cu ft)
SPK-8S2	8"	2Ω	200W - 500W (350W Ideal)	30 - 500 Hz	83.3836	8.5 mm	4.291 in	0.05 cu ft	0.5 - 1.0 (0.9 Ideal)	0.25 - 0.75 (0.5 Ideal)
SPK-8S4	8"	4Ω	200W - 500W (350W Ideal)	30 - 500 Hz	81.9876	8.5 mm	4.291 in	0.05 cu ft	0.5 - 1.0 (0.9 Ideal)	0.25 - 0.75 (0.5 Ideal)
SPK-10S2	10"	2Ω	300W - 700W (500W Ideal)	20 - 200 Hz	82.2488	14 mm	5.32 in	0.0626 cu ft	0.75 - 1.25 (1.0 Ideal)	0.75 - 1.15 (1.11 Ideal)
SPK-10S4	10"	4Ω	300W - 700W (500W Ideal)	20 - 200 Hz	83.7199	14 mm	5.32 in	0.0626 cu ft	0.75 - 1.25 (1.0 Ideal)	0.75 - 1.15 (1.11 Ideal
SPK-12S2	12"	2Ω	300W - 700W (500W Ideal)	20 - 200 Hz	84.6196	14 mm	6.14 in	0.0885 cu ft	1.25 - 2.75 (1.75 Ideal)	0.85 - 1.5 (1.0 Ideal)
SPK-12S4	12"	4Ω	300W - 700W (500W Ideal)	20 - 200 Hz	85.4588	14 mm	6.14 in	0.0885 cu ft	1.25 - 2.75 (1.75 Ideal)	0.85 - 1.5 (1.0 Ideal)









